Airquee Inflatables

To book your test please call +44 (0)1179 414 918 or visit www.airquee.com for more information.

Certificate Of Conformity to EN14960-1:2019

This certificate relates only to the individual product detailed below. It confirms that at the time of manufacture this product conforms to EN14960. To remain compliant this product must be tested annually.

This is the test certificate for your new inflatable. Please keep this in a safe place. This is valid for one year from the date below.



Product: MULTICOLOURED PARTY DOUBLE FRONT SLIDE MIDI BOUNCER (WITH AN EXTRA ARCH BIFF BASH)(VERSION 2)

Serial/Certificate no: P69958 **Code:** AQ10302PAMULTI

Tag No: 71565 **Valid From:** 19-11-2025 **Weight:** Unit: 126kg Total: 140kg

Structure	Pass	Fail	N/A	Notes
Trough Depth	X			Indoor Use Only: No Label Location: side Length: 6.20m Width: 5.3m Height: 2.76m Bed width panel: 0.46 Trough depth: 0.07 Inside wall height: 2.05 m FOH: 0.40 m Grounding weight: 85 Clamber net width: 0.00 Zips: 2 pcs (exterior velcro flap + interior non return flap) Netting: black scrim fixed Roof : black scrim fixed Artwork : printed (laminated, UV resistant)
Seam Security	X			
Stitching	X			
Walls & Towers	X			
Can Walls Contain Users	X			
Fall Off Height (FOH)	X			
Grounding	X			
Stability	X			
Entrapment	X			
Sharp Angles	X			
Zip(s)	X			
Windows			X	
Netting	X			
Clamber Netting			X	
Air Loss Points	X			
Markings	X			
Artwork	X			
Identification	X			

Materials	Pass	Fail	N/A	Notes
Fabric Material and Condition	X			Material : gloss 630g pvc + gloss 520g printable
Thread Condition	X			
Material Fire Retardancy	X			
De-lamitvation of PVC	X			

Anchorage	Pass	Fail	N/A	Notes
Total No of Anchors	X			Calculated Anchors: 8 Anchor points: 11 pcs PVC & metal triangle Bottom Supplied anchor accessories: 11 pcs / 400 mm* 18 mm metal pegs
Anchor Point Ingetrity	X			
Anchor Point Location	X			
Anchor Type	X			
Anchor Accessories	X			
Ropes			X	

Blower	Pass	Fail	N/A	Notes
Kilopascal (kPa)	X			kPa: 1.16 Blower minimum pressure: 1.00 Blower power: 1 pcs 1.5HP Blower tube length: 1.23 m Position: 1 pcs rear side
Size & Type	X			
Inlet & Outlet Mesh	X			
Cable & Plug	X			
Casing & Impeller	X			
Pat Test			X	
Return Flap	X			
Blower Tube(s) / Valve(s)	X			

Enterances, Exits & Evacuation	Pass	Fail	N/A	Notes
Deflation / Evacuation Time	X			Evacuation time(secs): 20 Enclosed Unit: Yes Platform height : 0.58m Step Length: 1.10m
Length of Step	X			

Totally Enclosed Structures	Pass	Fail	N/A	Notes
Exits			X	
Exit Markings			X	
Lighting Supports			X	
Emergency Lighting			X	
Deflation Speed			X	
User Area Pressure			X	

Slides	Pass	Fail	N/A	Notes
Wall Height / Platform Height	X			Platform wall height: 0.70 Platform wall height 1st metre: 0.70 Platform roof fitted: Yes Wall height: 0.7 m Platform height: 0.94 m Run out: 1 m Width of slide: 0.6 m Slide sheet: ice blue sliding material PVC
Run-Out	X			
Clamber Step	X			
Slide Sheet	X			

Users

Max User Height: 1.8 Max Users upto 1m: 12 Max Users upto 1.25m: 9 Max Users upto 1.5m: 8 Max Users over 1.8: 7

SIGNED BY: Oláh Etele Tibor
PIPA ANNUAL INFLATABLE INSPECTOR